

330 SPEEDY KING PRINTER

Model No : 330 SPEEDY KING PRINTER

Product Name : Inkjet Solvent Printer

FOB Port : NINGBO PORT

Payment terms: T/T, L/C or negotiate

Contact Person : Ms.Suaad Fan

Delivery Lead Time : 7-20days

View PDF file :  [330 SPEEDY KING PRINTER](#)

View Word file :  [330 SPEEDY KING PRINTER](#)



330 Speedy is the most valuable 3.2m wide format ink-jet printer. The new designed 3.2m solvent, eco-solvent based inkjet printer, based on an revolutionary new designed printer platform. Speedy equipped 12 pieces of new 126 nozzles 30pl piezo print heads(XAAR130/600 DPI) can achieve a great resolution up to 1440DPI and maximum output 61 m²/hr. With wave compensation feature of Aprint RIP, dedicted Aprint high density solvent ink, Speedy can achieve a good printing quality at 3 pass.

Resolution, Speed, Price are perfect to unify.

Features:

1. Equiped with XAAR130/600 DPI printheads.
2. USB2.0 high-speed data transport.
3. Automatic printheads heating system.
4. Double transmission media feeding rolls.
5. Reliable automatic solution cleaning system.
6. Front, middle and back media heating system.
7. Distinctively - Wavy printing, create excellent result.
8. 2-4mm adjustable height between printheads and media.
9. Air pumping system for ink pressure and printheads cleaning.
10. More than 6 years inkjet printer manufacturing experience, and moderb equipment production lines management, to ensure each machine is excellent.



Ningbo MEC Industry And Trade Co., Ltd.

Tel : 0086-574-66831478/ 87383760

Fax : 0086-574-87383750

Email : sales@nbmec.com , sales@signmaker.cn

Website : www.nbmec.com , www.signmaker.cn

330 SPEEDY KING(12 HEADS) XAAR 130 600DPI OUTDOOR PRINTER	
Print Technique	Xaar 130 600Dpl, 12 heads
Printing Quality	Photo effect up to 1440DPI
Max Printing Width	3250mm
Max Media Width	3300mm
Media Type	PVC, Flex, vinyl, window film, polyester, etc.
Ink Type	Solvent-Eco solvent base ink: C, M, Y, K
Color	4 colors
Output (12 heads)	3pass, 61m ² /h
	4pass, 44m ² /h
	6pass, 29m ² /h
	8pass, 22m ² /h
Printing Driver	Aprint Rip, Onyx, Scanvec, Wasatch Rip supported
Media Transmission	Roll media less than 50kg/roll, Auto feeding
Printhead Height	2mm - 4mm above media adjustable
Pre-heater	Auto heating after electrifying, the tiptop temperature is about 40°C
Noise	Printing status ≤70dB, Waiting status ≤40dB(ISO7779)
Printer Size (including ink tank) / Net Weight	L3,950mm x W800mm x H1,120mm / 330kg
Package Size / Weight	L4,500mm x W925mm x H1,200mm / 368kg
Input Voltage	AC 100-240V, 50HZ/60HZ
Power (AC 200V applied)	Print: ≤3A, Heating: ≤5A
Working Environment	Temperature: 20°C-28°C, Humidity: 40%-70%

Address : 2/F, A29 Zone, Alley 166, Huancheng North Rd. (West Section), Jiangbei

District, Ningbo, Zhejiang, China Postal code: 315020

Tel: (86) 574 66831478/87383760, Fax: (86) 574 87383750